GC Application ID No.: 15433



Weathered Gasoline on ZB-5MS

		15						
Zebron [™] ZB-5MS, GC Cap. Column 30 m x 0.25 mm x 0.50 µm, Ea 5% Phenyl-Arylene 95% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.5 µm 7HG-G010-17 35°C for 6 min to 300°C at 6°C/min						Construction of the second sec		
Constant Flow Helium, 1.2 mL/min								
Flame Ionization (FID) (300°C)						RUD TOO Awards Products used in this application:		
11								
						Zek		
Under				W.M. M.	Mleman			
5	10	15	20	25	30	min		
	Zebron [™] ZB-5I 5% Phenyl-Ary 30 meters x 0.3 7HG-G010-17 35°C for 6 min Constant Flow I Split 10:1 1 µL Flame Ionizatio	Zebron [™] ZB-5MS, GC Cap. 5% Phenyl-Arylene 95% Di 30 meters x 0.25 mm x 0.5 7HG-G010-17 35°C for 6 min to 300°C at Constant Flow Helium, 1.2 m Split 10:1 1 µL @ 275°C Flame Ionization (FID) (300	5% Phenyl-Arylene 95% Dimethylpolysika 30 meters x 0.25 mm x 0.5 μm 7HG-G010-17 35°C for 6 min to 300°C at 6°C/min Constant Flow Helium, 1.2 mL/min Split 10:1 1 μL @ 275°C Flame Ionization (FID) (300°C)	Zebron [™] ZB-5MS, GC Cap. Column 30 m x 0.25 mm x 0 5% Phenyl-Arylene 95% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.5 μm 7HG-G010-17 35°C for 6 min to 300°C at 6°C/min Constant Flow Helium, 1.2 mL/min Split 10:1 1 μL @ 275°C Flame Ionization (FID) (300°C)	Zebron [™] ZB-5MS, GC Cap. Column 30 m x 0.25 mm x 0.50 μm, Ea 5% Phenyl-Arylene 95% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.5 μm 7HG-G010-17 35°C for 6 min to 300°C at 6°C/min Constant Flow Helium, 1.2 mL/min Split 10:1 1 μL @ 275°C Flame Ionization (FID) (300°C)	Zebron [™] ZB-5MS, GC Cap. Column 30 m x 0.25 mm x 0.50 μm, Ea 5% Phenyl-Arylene 95% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.5 μm 7HG-G010-17 35°C for 6 min to 300°C at 6°C/min Constant Flow Helium, 1.2 mL/min Split 10:1 1 μL @ 275°C Flame Ionization (FID) (300°C)	Zebron [™] ZB-SMS, GC Cap. Column 30 m x 0.25 mm x 0.50 µm, Ea 5% Phenyl-Arylene 95% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.5 µm 7HG-6010-17 35°C for 6 min to 300°C at 6°C/min Constant Flow Helium, 1.2 mL/min Split 10:1 1 µL @ 275°C Flame Ionization (FID) (300°C) Products used in	

ANALYTES:

1 Gasoline

©2025 Phenomenex Inc. All rights reserved.

Phenomenex products are available worldwide.

www.phenomenex.com

For more information contact your Phenomenex Representative at support@phenomenex.com