GC Application



Organotins by MSD on a ZB-5MS

Organotins by MSD on a 2B-SMS				
Column: Phase: Dimensions: Order No: Oven Profile:	Zebron [™] ZB-5MS, GC Cap. Column 30 m x 0.25 mm x 0.25 µm, Ea 5% Phenyl-Arylene 95% Dimethylpolysiloxane 30 meters x 0.25 mm x 0.25 µm 7HG-G010-11 60 °C for 2 min to 270 °C at 10 °C/ min for 5 min			Construction of Construction
Carrier Gas: Injection: Detection: Analyst Note:	Constant Flow He, 1.3 mL/min Splitless 20:1 1 μ L @ 240°C Mass Selective (MSD) (230°C) MSD: sim mode 121,179,235 m/z The analytes are 10ppm, simultaneous L:L extraction and derivatization using Sodium Tetraethylborate.			Products used in this application:
16732				Zebron
	1	3		



ANALYTES:

- 1 Monobutyltin
- 2 Tripropyltin
- 3 Dibutyltin
- Tributyltin 4
- 5 Tetrabutyltin

©2025 Phenomenex Inc. All rights reserved.

Phenomenex products are available worldwide.

www.phenomenex.com

For more information contact your Phenomenex Representative at support@phenomenex.com