

FMOC-DL-Lysine-(boc)-OH on Lux 5 µm Cellulose-2 250 x 4.6mm in NP

Column: Lux® 5 µm Cellulose-2, LC Column 250 x 4.6 mm, Ea

Dimensions: 250 x 4.6 mm ID

Order No: 00G-4457-E0

Elution Type: Isocratic

Eluent A: 0.1% TFA in Hexane

Eluent B: 0.1% TFA in IPA

| Gradient Profile: | Step No. | Time (min) | Pct A | Pct B |
|-------------------|----------|------------|-------|-------|
| | 1 | 20 | 85 | 15 |

Flow Rate: 1 mL/min

Col. Temp.: ambient

Detection: UV-Vis Abs.-Variable Wave.(UV) @ 254 nm (ambient)

Analyst Note: SecurityGuard™ Guard Cartridge System extends column lifetime.

- SecurityGuard Cartridges, Lux Cellulose-2, 4 x 3.0mm ID, 10/Pk Part No.: AJ0-8366


- Holder Part No.: KJ0-4282



Products used in this application:



18734



ANALYTES:

1 FMOC-Lys(Boc)-OH

Retention Time: 12.5 min

2 FMOC-Lys(Boc)-OH

Retention Time: 16.1 min

