HPLC Application

ID No.: 23841



Underivatized MMA and Succinic Acid from Plasma on Luna Omega 1.6u PS C18, 50x2.1mm with Strata-X-AW

Luna Omega 1.6u PS C18 100A, LC Column 50 x 2.1 mm, Ea

50 x 2.1 mm ID **Dimensions:** Order No: 00B-4752-AN Elution Type: Gradient

Eluent A: 0.1% Formic Acid in H2O Eluent B: 0.1% Formic Acid in ACN

Gradient	Step No.	Time (min)	Pct A	Pct B
Profile:	1	0	98	2
	2	2	10	90
	3	3	10	90
	4	3.01	98	2
	5	5	98	2



Products used in this application:



Flow Rate: 0.4 mL/min

Col. Temp.: 40 °C

Analyst Note:

Detection: Tandem Mass Spec (MS-MS) @ (600 °C)

Detector Info: <a target="_blank"

href="https://sciex.com/products/mass-spectrometers?utm_campaign=2019%20application%20search&utm_source=phenomenex&utm_medium=referral">SCIEX<MMA (117.0-->72.9; 117.0-->54.9)

MMA-D3 (120.1-->75.9)

23841 1.4e5 1.3e5 1.2e5 1.1e5 1.0e5 § 9.0e4 ₹ 8.0e4 훧 7.0e4 6.0e4 5.0e4 4.0e4

ANALYTES:

Interference

3.0e4 2.0e4 1.0e4 0.0

Retention Time: 0.741 min

Succinic Acid

Retention Time: 0.945 min

3 MMA

Retention Time: 1.26 min

©2025 Phenomenex Inc. All rights reserved.

For more information contact your Phenomenex Representative at support@phenomenex.com



3.0

Sample Preparation Details

for HPLC Application ID No.: 23841



Underivatized MMA and Succinic Acid from Plasma on Luna Omega 1.6u PS C18, 50x2.1mm with Strata-X-AW

PRODUCT DESCRIPTION:

Strata™-X-AW 33 µm Polymeric Weak Anion, 30 mg / 1 mL, Tubes , 100/Pk

Order No.: 8B-S038-TAK

SOLID PHASE EXTRACTION (SPE) PRODCEDURE:

Note: The solvent volumes shown below are for a 30 mg bed mass.

The solvent volumes will need to be adjusted for a smaller or larger bed mass.

_							
•	^	-	а	iti	_	-	

Load:

- 1. Into individually labeled 1.5 mL conical micro-centrifuge tubes, combine 0.5 mL of 0.1% acetic acid, 50 µL IS, and 100 µL blank, standard, or sample.
- 2. Activate the SPE cartridge (Strata-X-AW, 30 mg/1mL) with 1 mL pure methanol.

Inject: 10 µL on HPLC Tandem Mass Spec (MS-MS) @ (600°C)

- 3. Equilibrate the SPE cartridge with 1 mL of 0.1% acetic acid.
- 4. Load sample and proceed with elution.
- 5. Wash the SPE cartridge with 0.5 mL 50% methanol.
- 6. Dry the SPE bed under high vacuum for 5-10 min.
- 7. Elute the analyte with 2 x 0.600 mL 2% ammonium hydroxide in methanol.
- 8. Evaporate the tubes in a concentrator at 45-50°C.
- 9. Remove the tubes and resuspend the residue in 200 μ L Mobile Phase A (0.1% formic acid).

Wash:	
Dry:	
5-10 min under high vacuum	
Elute:	
Final Prep and Analysis:	

ANALYTES:	Spiked Conc.	Log P	рКа	% Rec	%RSC
	(ng/mL)				(n=0)
1 Interference	0				
2 Succinic Acid	0				
3 MMA	0				

Note: This method is designed as a convenient starting point for further investigation and can be tailored to meet your extraction goals. Call your local Phenomenex Representative for assistance in method development and optimization techniques.

©2025 Phenomenex Inc. All rights reserved.

For more information contact your Phenomenex Representative at support@phenomenex.com



Phenomenex products are available worldwide.

www.phenomenex.com support@phenomenex.com